




WHITE BODY GVT  
**PORCELAIN TILES**


600x  
**600MM**





RUSTIC SERIES





RUSTIC SERIES



LIGHT



RUSTIC SERIES



DARK



7051


LIGHT




RUSTIC SERIES



DARK



7052




RUSTIC SERIES






RUSTIC SERIES



DARK



RUSTIC SERIES



DECOR 1


7055



# Digital

PORCELAIN TILES  
600x600mm

DARK



RUSTIC SERIES



DECOR 1

7056




DIGITAL  
PRINTING




RECTIFIED




ECO FRIENDLY




RUSTIC SERIES







RUSTIC SERIES







RUSTIC SERIES







RUSTIC SERIES





RUSTIC SERIES





RUSTIC SERIES





RUSTIC SERIES








RUSTIC SERIES






RUSTIC SERIES







RUSTIC SERIES






RUSTIC SERIES






RUSTIC SERIES






RUSTIC SERIES





RUSTIC SERIES





RUSTIC SERIES





RUSTIC SERIES



# TECHNICAL SPECIFICATION

Particulars	Standard as per ISO 13006/EN 176	OUR VALUE	METHOD OF TESTING
Deviation in length	± 0.50%	± 0.3%	EN 98
Deviation in Thickness	± 5%	± 3%	EN 98
Straightness Of Sides	± 0.5%	± 0.3%	EN 98
Rectangularity	± 0.6%	± 0.3%	EN 98
Surface Flatness	± 0.5%	± 0.3%	EN 98
Water Absorption	< 3	3 < 4	ISO 10945.3 EN 98
Mohs Hardness	> 5	> 5	EN 101
Flexural Strength	> 35 N/Sq.mm	> 39 N/Sq.mm	—
Abrasion Resistance	As specified by Manufacturer	PE   3	ISO 10545.6 EN 102
Frost Resistance	Frost Proof	Frost Proof	ISO 10534 - 11
Chemical Resistance	No Damage	No Damage	ISO 10534 - 18
Thermal Shock Resistance	No Damage	No Damage	ISO 10545 - 9
Colour Resistance	No Damage	No Damage	—
Stain Resistance	Resistance	Stain Proof	ISO 10545 - 14
Moisture Expansion	NIII	NIII	ISO 10545 - 10
Crazing Resistance	Min 2 Cycle	Min 4 Cycle	—

Note : Colour Shown are as accurate as the limitations of the printing process will allow. Prospective Customer Are advised to inspect a sample of the tiles before ordering every effort has been made to ensure the Accuracy of the information given. However, the Company reserves the right to change the specifications without prior notice. Sometimes variations in shade or size being inherent to ceramic industry may occur. Before fixing, we advice you to follow the fixing Instruction on the cartons of the tiles as on responsibility can be accepted by the company once the tiles have been fixed.

## PACKING DETAIL

Size	Thickness	No. of Tiles	Area Approx.	Weight Approx.
600 X 600 MM	9 MM	4 Pcs.	1.44 Sq. Mtr.	28 Kg.

## UTILITY OF FLOOR TILES



Airport Terminals



Discotheques



Corridors/Halls



Industries



Gymnasiums



Hospitals



Religious Places



Hotels



Offices



Super Markets



Schools



Shopping malls



Restaurants



Domestic